

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)


PCT

(10) International Publication Number
WO 2005/019088 A1

- (51) International Patent Classification⁷: **B66D 1/30**
- (21) International Application Number:
PCT/NL.2004/000561
- (22) International Filing Date: 10 August 2004 (10.08.2004)
- (25) Filing Language: Dutch
- (26) Publication Language: English
- (30) Priority Data:
1024079 11 August 2003 (11.08.2003) NL
- (71) Applicant (for all designated States except US): NO-VATUG B.V. [NL/NL]; P.O. Box 23384, NL-3001 KJ Rotterdam (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): VAN DER LAAN, Markus [NL/NL]; Johan Evertsenlaan 18, NL-2341 SV Oegstgeest (NL).
- (74) Agent: VAN WESTENBRUGGE, Andries et al.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: RETAINING DEVICE FOR A CABLE



(57) Abstract: Retaining device for a cable (4). This consists of a rotary drum (2) around which at least two cable windings are made, retaining and paying out being possible by means of a motor (10) that drives the drum. According to the present invention the axis (12) of rotation for the drive is offset with respect to the axis of the drum, so that in a certain position the axis (12) of rotation is essentially coincident with the casing face of the drum engaging on the cable.

WO 2005/019088 A1



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments*

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

BEST AVAILABLE COPY